



**AK(Z) 1110/.. - 5,0 (5,08) - green**

**AKZ 1200/.. - 5,08 - green**

**2-20 (16) poles, Spacing 5,0 mm or 5,08 mm  
insert required no. of poles ..**

**2-24 poles, Spacing 5,08 mm  
insert required no. of poles ..**

**Ratings:**

	(BU 04) 	(BU 04) 	(BU 04) 
	UL 1059	CSA 22.2 No. 158	DIN VDE 0627
<b>Rated Voltage</b>	300 V	300 V	250 V
<b>Rated Current</b>	15 A	12 A	12 A (T60)
<b>Wire Size</b>	AWG 22-10	AWG 22-10	2,5 mm <sup>2</sup>
<b>Rating Impulse Voltage/Dirt Level</b>			4 kV/3
<b>Rated Torque / Screw Size</b>			0,5 Nm/M3
<b>Max. Rated Cross Section</b>			
Single Wire (solid)			2,5 mm <sup>2</sup>
Stranded Wire (flexible)			2,5 mm <sup>2</sup>
Stranded wire with Ferrules			2,5 mm <sup>2</sup>

**Ratings:**

	UL 1059	CSA 22.2 No. 158	DIN VDE 0627
<b>Rated Voltage</b>	300 V	300 V	250 V
<b>Rated Current</b>	15 A	15 A	12 A (T60)
<b>Wire Size</b>	AWG 22-12	AWG 22-12	2,5 mm <sup>2</sup>
<b>Rating Impulse Voltage/Dirt Level</b>			4 kV/3
<b>Rated Torque / Screw Size</b>			0,5 Nm/M2,5
<b>Max. Rated Cross Section</b>			
Single Wire (solid)			2,5 mm <sup>2</sup>
Stranded Wire (flexible)			2,5 mm <sup>2</sup>
Stranded wire with Ferrules			2,5 mm <sup>2</sup>

**Dimensions**

Spacing	5,0 mm (5,08 mm)
Stripped Length	7,0 mm

**Materials**

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Terminal Block	CuZn
Contact	CuSn
Colour	RAL 6018

**Dimensions**

Spacing	5,08 mm
Stripped Length	10,0 mm

**Materials**

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Clamp cage	Fe/Fe
Contact	CuSn
Colour	RAL 6018