



AKZ 1700/.. - 3,81 - green

**2-20 poles, Spacing 3,81 mm
insert required no. of poles ..**



AKZ 1710/.. - 3,81 - green

**2-20 poles, Spacing 3,81 mm
insert required no. of poles ..**

Ratings:

* Approval pending

	*	*	*
	UL 1059	CSA 22.2 No. 158	DIN VDE 0627
Rated Voltage	300 V	300 V	160 V
Rated Current	8 A	8 A	9 A (T60)
Wire Size	AWG 28-16	AWG 28-16	1,5 mm²
Rating Impulse Voltage / Dirt Level			4 kV/3
Rated Torque / Screw Size			0,4 Nm/M2
Max. Rated Cross Section			
Single Wire (solid)			1,5 mm²
Stranded Wire (flexible)			1,0 mm²
Stranded wire with Ferrules			1,0 mm²

Dimensions

Spacing	3,81 mm
Stripped Length	7,0 mm

Materials

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Terminal Block	CuZn
Contact	CuSn
Colour	green
	RAL 6018

Ratings:

* Approval pending

	*	*	*
	UL 1059	CSA 22.2 No. 158	DIN VDE 0627
Rated Voltage	300 V	300 V	160 V
Rated Current	8 A	8 A	9 A (T60)
Wire Size	AWG 28-16	AWG 28-16	1,5 mm²
Rating Impulse Voltage / Dirt Level			4 kV/3
Rated Torque / Screw Size			0,4 Nm/M2
Max. Rated Cross Section			
Single Wire (solid)			1,5 mm²
Stranded Wire (flexible)			1,0 mm²
Stranded wire with Ferrules			1,0 mm²

Dimensions

Spacing	3,81 mm
Stripped Length	7,0 mm

Materials

Insulating Material	PA
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Terminal Block	CuZn
Contact	CuSn
Colour	green
	RAL 6018